

RGB LED FLEX STRIP

Model: FA60M50-XM-24V-RGB



MODEL

FA60M50-XM-24V-RGB

- COLOR (Red, Green, Blue)
- VOLTAGE (24V)
- LENGTH (2 Meters, 6 Meters)
- LED TYPE (5050 SMD)
- LED/METER (60 LED/Meter)
- COVER TYPE (Type A, no coating)
A=IP22 B=IP62 C=IP64
- FLEX STRIP

24V
DC Power

4.4
WATTS
FOOT

**SUPER
BRIGHT**
RGB

UL US
LISTED
use only with
Class 2 Type
power units

flexible

VIEW ANGLE
120°

25,000+
HOURS

RoHS

TRIMMABLE

**COLOR
CHANGING**

STATIC ELECTRICITY
CAN DAMAGE
PRODUCT



BENEFITS

- Color Changing RGB
- View Angle 120°
- Double sided 3M Tape backing
- Ultra bright surface - mount LEDs
- Low power consumption and little heat
- No RF interference
- Long life of LEDs
- Flexible RGB LED strip lights
- Solid-state lighting
- Continuous length
- Can be cut to size at marked intervals (Qualified personnel)

APPLICATIONS

- Store Fixture shelving
- Architectural accenting
- Backlighting of glass and acrylic
- Corporate showrooms and exhibition displays
- Optional aluminum mounting channel with clear and diffused lens

SPECIFICATIONS

Roll Size	2m (6.56ft) / 6m (19.68 Feet)
Max Voltage	24 VDC (regulated/Class 2)
Watt Foot	4.4 (3.6 Amps-6m roll, 2.1 Amps-2m roll)
Light Source	60 pcs/Meter (39.37") 5050 SMD LED
Dimensions	10(W) x 2.5(H)mm (3/8" x 3/32")
Max Length	2m (6.56ft) / 6m (19.68 Feet)
View Angle	120°
Max Current	180mA/foot
Bend Radius	4 inches (100mm) Max, one flat plane
Lamp Life	>25,000 hours (average life)
IP Rating	IP22 Type A
Mount	Smooth Surface/burrows free
Operating Temperature	-25°C ~ +40°C

OPTIONAL ACCESSORIES

XLD200B-224V-FC (24VDC) One Channel Output-Class 2	H-DMX2108A-5M-3 DMX color controller	HUEDA™
		

Check out website product page for more color controllers, power supply and accessories options

DIAGRAM

