96W 24V Class 2 Triac / 0-10V Dimmable Driver

Model : MD-024-096VTDHV2

LED WORLD INC
ledworldlighting.com | ledworld.ca
1-800-387-4081

24V DC | 96W | cULus LISTED | FC | SELV | SMOOTH DIMMABLE | 6 Years Limited Manufacturer Warranty

FEATURES

- Constant Voltage Output
- Universal AC input: 100~277VAC
- Power Factor > 0.98
- High efficiency > 86%
- Protection : Short circuit / Over Loading / Over temperature
- Suitable for use in dry, damp and wet indoor/outdoor locations
- Easy installation
- Free Air convection cooling
- Compatible with leading edge and trailing edge Triac Dimmers
- Flicker-free dimming
- Capable of 1% dimming using 0-10V PWM dimming technology
- Full protection aluminum housing
- cULus listed
- Meets California Title 24 standard
- Suitable for LED lighting and sign lighting applications
- 8 knockouts for easy wiring

SPECIFICATIONS

Output	DC Voltage	24V
	Voltage Tolerance	±0.5V
	Rated Current	4.0A
	Rated Power	96W
Input	Voltage Range	100~277VAC
	Frequency Range	47~63Hz
	Power Factor (Typ.)	PF ≥ 0.98/120V, PF ≥ 0.95/277V
	Efficiency (Typ.)	83% @ 120VAC, 86% @ 277VAC
	AC Current (Typ.)	1.3A @ 100VAC
	Leakage Current	< 0.50mA
	Inrush Current	20A. 50%, 1.6ms
	THD	<20%
Protection	Over Temp.	100°C±10°C shut down o/p voltage, recovers automatically after cooling
	Short Circuit	Hiccup mode, recovers automatically after fault condition is removed
	Over Loading	≤ 120% constant current limiting, auto-recovery
Environment	Working Temp.	-40°C ~ 60°C (-40°F ~ 140°F)
	Working Humidity	20~90 % RH, non-condensing
	Storage Temp. Humidity	-40°C ~ 80°C, 10~95 % RH
	Temp. Coefficient	±0.03% / °C (0°~50°C)
	Vibration	10~500Hz, 5G 10min/1 cycle, period for 60min each along X, Y, Z axes
Safety & EMC	Safety standards	UL8750 CAN/CSA-C22.2 NO.250.13
	Withstand voltage	I/P-O/P:3.75KVAC
	Isolation Resistance	I/P-O/P: 100MΩ/500VDC/25°C/70%RH
	EMC EMISSION	FCC Part 15 B
Other	Net. Weight	1.3Kg (2.86lbs)
	Size	220L x 95W x 41H mm (8.66" x 3.7" x 1.61")

LED World Inc. | #130 10615 48 ST SE | CALGARY, AB T2C 2B7 | CANADA | Version 1.3 02/04/26

Copyright © 2026 LED WORLD INC™. All Rights Reserved. We are not responsible for errors or omissions. Product and specifications subject to change without notice. Registered trademarks are owned by their respective registers, or licensee(s).

96W 24V Class 2 Triac / 0-10V Dimmable Driver

Model : MD-024-096VTDHV2

PRODUCT DIMENSION



KNOCKOUTS



DIMMING OPERATION

- The Pulse-Width Modulation (PWM) of output voltage can be adjusted through input terminal of the AC phase line(L) by connecting a triac dimmer
- Match with leading edge Triac Dimmer (Can customized as a driver only matching trailing edge Triac Dimmers if needed)
- Use dimmers with power at least 2.5 times as the output power of the driver
- For forward phase, magnetic low voltage and Triac dimmers
- 0-10V Dimming: Dim(+) Purple wire to 0-10V dimmer signal(+), Dim(-) Grey wire to 0-10V dimmer signal(-)

WARNING

- Check polarity
- Risk of Electric Shock.
- Risk of Fire. Installation involves special wiring methods to run wiring through a building structure. Consult a qualified electrician.
- Risk of Electric Shock. Mount the unit at a height more than 1 ft (30cm) from the ground

LED World Inc. | #130 10615 48 ST SE | CALGARY, AB T2C 2B7 | CANADA | Version 1.3 02/04/26

Copyright © 2026 LED WORLD INC™. All Rights Reserved. We are not responsible for errors or omissions. Product and specifications subject to change without notice. Registered trademarks are owned by their respective registers, or licensee(s).